

VALERA AT

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
P235/70R16	104T	520 A B	AP368	7.0	6.0 - 8.0	1984	44	13.48	28.98	9.45	31.59	BSW
P255/70R16	109T	520 A B	AP374	7.5	6.5 - 8.5	2271	44	13.48	30.08	10.24	34.57	BSW
P265/70R16	111T	520 A B	AP365	8.0	7.0 - 9.0	2403	44	13.48	30.63	10.71	35.8	BSW
P265/75R16	114T	520 A B	AP369	7.5	7.0 - 9.0	2601	44	13.48	31.65	10.51	38.27	BSW
P245/65R17	105T	520 A B	AP372	7.0	7.5 - 8.5	2039	44	13.48	29.53	9.76	32.98	BSW
P245/70R17	108T	520 A B	AP373	7.0	6.5 - 8.0	2205	44	13.48	30.55	9.76	35.03	BSW
P265/70R17	113T	520 A B	AP364	8.0	7.0 - 9.0	2535	44	13.48	31.65	10.71	36.75	BSW
P275/65R18	114T	520 A B	AP371	8.0	7.5 - 9.5	2601	44	13.48	32.09	10.98	39.7	BSW
P275/60R20	114T	520 A B	AP370	8.0	7.5 - 9.5	2601	44	13.48	32.99	10.98	39.9	BSW
31X10.50R15LT	109S		AP366	8.5	7.0 - 9.0	2270	50	15.87	30.51	10.55	40.19	BSW
LT225/75R16	115/112S		AP376	6.0	6.5 - 7.0	2680/2470	80	15.87	29.29	8.78	38.29	BSW
LT265/75R16	123/120T		AP377	7.5	7.0 - 8.0	3415/3085	80	15.87	31.65	10.51	48.39	BSW
LT285/75R16	126/123R		AP375	8.0	7.5 - 8.5	3750/3415	80	15.87	32.83	11.26	53.33	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall

Primewell reserves the right to change construction, materials or specifications without notice or obligation.