

VALERA HT

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
P225/70R15	100T	600 A B	AP362	6.5	6.0 - 7.5	1753	44	10.33	27.44	8.98	26.5	BSW
P225/75R15	102T	600 A B	AP361	6.0	6.0 - 7.5	1874	44	10.33	28.31	8.78	27.62	BSW
P235/75R15	105T	600 A B	AP320	6.5	6.0 - 8.0	2028	44	10.33	28.86	9.25	29.83	BSW
P215/70R16	99S	600 A B	AP318	6.5	5.5 - 7.0	1709	44	10.33	27.87	8.7	25.2	BSW
P225/70R16	101S	600 A B	AP333	6.5	6.0 - 7.5	1819	44	10.33	28.43	8.98	28.35	BSW
P235/70R16	104T	600 A B	AP317	7.0	6.0 - 8.0	1984	44	10.33	28.98	9.45	30.4	BSW
P245/70R16	106S	600 A B	AP321	7.0	6.5 - 8.0	2094	44	10.33	29.53	9.76	31.2	BSW
P255/70R16	109S	600 A B	AP322	7.5	6.5 - 8.5	2271	44	10.33	30.08	10.24	33.09	BSW
P265/70R16	111T	600 A B	AP355	8.0	7.0 - 9.0	2403	44	10.33	30.63	10.71	34.92	BSW
P225/75R16	106S	600 A B	AP337	6.0	6.5 - 7.5	2094	50	10.33	29.29	8.78	29.67	BSW
P235/75R16	109S	600 A B	AP329	6.5	6.0 - 8.0	2271	50	10.33	29.84	9.25	31.86	BSW
P245/75R16	109S	600 A B	AP332	7.0	6.5 - 8.0	2271	44	10.33	30.47	9.76	32.98	BSW
P265/75R16	114T	600 A B	AP356	7.5	7.0 - 9.0	2601	44	10.33	31.65	10.51	37.08	BSW
225/65R17	102H	600 A B	AP335	6.5	6.0 - 8.0	1874	44	10.33	28.5	8.98	27.34	BSW
P235/65R17	103T	600 A B	AP319	7.0	6.5 - 8.5	1929	44	10.33	29.06	9.45	28.04	BSW
P245/65R17	105T	600 A B	AP353	7.0	7.0 - 8.5	2039	44	10.33	29.53	9.76	31.86	BSW
P265/65R17	110T	600 A B	AP328	8.0	7.5 - 9.5	2337	44	10.33	30.55	10.71	34.39	BSW
P245/70R17	108T	600 A B	AP354	7.0	6.5 - 8.0	2205	44	10.33	30.55	9.76	33.22	BSW
P265/70R17	113T	600 A B	AP323	8.0	7.0 - 9.0	2535	44	10.33	31.65	10.71	37.08	BSW
255/55R18	109H	600 A B	AP343	8.0	7.0 - 9.0	2271	50	10.33	29.02	10.43	32.56	BSW
235/60R18	103V	600 A B	AP351	7.0	6.5 - 8.5	1929	44	10.33	29.09	9.45	30.29	BSW
245/60R18	105H	600 A B	AP341	7.0	7.0 - 8.5	2039	44	10.33	29.57	9.76	32.72	BSW
P265/60R18	109T	600 A B	AP327	8.0	7.5 - 9.5	2271	44	10.33	30.51	10.71	35.82	BSW
235/65R18	106H	600 A B	AP352	7.0	6.5 - 8.5	2094	44	10.33	30.04	9.45	31.08	BSW
P255/65R18	109T	600 A B	AP350	7.5	7.0 - 9.0	2271	44	10.33	31.06	10.24	33.77	BSW
P265/65R18	112S	600 A B	AP345	8.0	7.5 - 9.5	2469	44	10.33	31.54	10.71	35.93	BSW
P275/65R18	114T	600 A B	AP330	8.0	7.5 - 9.5	2601	44	10.33	31.65	10.71	38.76	BSW
P255/70R18	112T	600 A B	AP347	7.5	6.5 - 8.5	2469	44	10.33	32.09	10.24	36.02	BSW
P265/70R18	114S	600 A B	AP346	8.0	7.0 - 9.0	2601	44	10.33	32.64	10.71	37.96	BSW
P245/55R19	103S	600 A B	AP348	7.5	7.0 - 8.5	1929	44	10.33	29.65	9.96	32.5	BSW
P255/60R19	108H	600 A B	AP342	7.5	7.0 - 9.0	2205	44	10.33	31.06	10.24	33.77	BSW
275/45R20	110H	600 A B	AP326	9.0	8.5 - 10.5	2337	50	10.33	29.76	10.75	35.14	BSW
265/50R20	107V	600 A B	AP363	8.5	8.0 - 9.0	2150	44	10.58	30.47	10.91	37.21	BSW
P275/55R20	111H	600 A B	AP325	8.5	7.5 - 9.5	2403	44	10.33	31.89	11.18	39.04	BSW
P275/60R20	114T	600 A B	AP331	8.0	7.5 - 9.5	2601	44	10.33	32.99	10.98	39.02	BSW
31X10.50R15LT	109R		AP339	8.5	7.5 - 9.0	2270	50	12.85	30.51	10.55	40.83	BSW
LT225/75R16	115/112S		AP357	6.0	6.0 - 7.0	2680/2470	80	12.85	29.29	8.78	37.3	BSW
LT245/75R16	120/116S		AP358	7.0	6.5 - 8.0	3042/2778	80	12.85	30.47	9.76	42.75	BSW
LT265/75R16	123/120S		AP360	7.5	7.0 - 8.0	3415/3085	80	12.85	31.65	10.51	48.77	BSW
LT285/75R16	126/123R		AP334	8.0	7.5 - 8.5	3750/3415	80	12.85	32.83	8.11	53.75	BSW
LT215/85R16	115/112R		AP338	6.0	5.5 - 7.0	2680/2470	80	12.85	30.39	8.5	39.07	BSW
LT235/85R16	120/116R		AP340	6.5	6.0 - 7.5	3042/2778	80	12.85	31.73	9.25	43.28	BSW
LT245/70R17	119/116S		AP349	7.0	6.5 - 8.0	3000/2755	80	12.85	30.55	9.76	41.91	BSW
LT265/70R17	121/118S		AP359	8.0	7.5 - 8.5	3195/2910	80	12.85	31.65	10.71	48.04	BSW
LT285/70R17	121/118R		AP324	8.5	7.5 - 9.0	3195/2910	65	12.85	32.76	11.5	52.27	BSW
LT245/75R17	121/118R		AP336	7.0	6.5 - 7.5	3195/2910	80	12.85	31.5	9.76	45.17	BSW
LT235/80R17	120/117R		AP344	6.5	6.0 - 7.5	3085/2835	80	12.6	31.81	9.25	42.7	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Side Wall

Primewell reserves the right to change construction, materials or specifications without notice or obligation.