VALERA AT²

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
235/75R15	105S	520 A B	VAT2002	6.5	6.0 - 8.0	2039	44	13	28.9	9.3	31.1	OWL
235/70R16	104T	520 A B	VAT2003	7.0	6.0 - 8.0	1984	44	13	29.0	9.5	30.9	OWL
265/70R16	111T	520 A B	VAT2005	8.0	7.0 - 9.0	2403	44	13	30.6	10.7	35.9	OWL
245/75R16	109T	520 A B	VAT2004	7.0	6.5 - 8.0	2271	44	13	30.5	9.8	34.2	OWL
245/65R17	105T	520 A B	VAT2012	7.0	7.0 - 8.5	2039	44	13	29.5	9.8	32.8	OWL
265/65R17	110T	520 A B	VAT2014	8.0	7.5 - 9.5	2337	44	13	30.6	10.7	36.6	OWL
265/70R17	113T	520 A B	VAT2015	8.0	7.0 - 9.0	2535	44	13	31.7	10.7	36.9	OWL
285/70R17	117T	520 A B	VAT2016	8.5	7.5 - 9.5	2833	44	13	32.8	11.5	43.7	OWL
265/60R18	109T	520 A B	VAT2022	8.0	7.5 - 9.5	2271	44	13	30.5	10.7	37.9	OWL
265/65R18	112S	520 A B	VAT2023	8.0	7.5 - 9.5	2469	44	13	31.5	10.7	38.6	OWL
275/65R18	114T	520 A B	VAT2025	8.0	7.5 - 9.5	2601	44	13	32.1	11.0	39.2	OWL
265/70R18	114S	520 A B	VAT2024	8.0	7.0 - 9.0	2601	44	13	32.6	10.7	39.2	OWL
275/55R20	111H	520 A B	VAT2029	8.5	7.5 - 9.5	2403	44	13	31.9	11.2	41.2	BSW

Tire Size	LI / SR (s/d)	Load Range / Ply Rating	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
31X10.50R15LT	109S	C	VAT2001	8.5	7.0 - 9.0	2270	50	16	30.5	10.6	41.7	OWL
LT235/85R16	120/116S	E	VAT2007	6.5	6.0 - 7.5	3042/2778	80	16	31.7	9.3	44.5	OWL
LT245/75R16	120/116S	E	VAT2008	7.0	6.5 - 8.0	3042/2778	80	16	30.5	9.8	44.5	OWL
LT265/75R16	123/120S	E	VAT2009	7.5	7.0 - 8.0	3415/3085	80	16	31.7	10.5	49.6	OWL
LT285/75R16	126/123R	E	VAT2010	8.0	7.5 - 9.0	3750/3415	80	16	32.8	11.3	52.7	OWL
LT235/80R17	120/117S	E	VAT2017	6.5	6.0 - 7.5	3085/2835	80	16	31.8	9.3	45.9	OWL
LT245/70R17	119/116S	E	VAT2018	7.0	6.5 - 8.0	3000/2755	80	16	31.5	9.8	44.1	OWL
LT265/70R17	121/118S	E	VAT2020	8.0	7.0 - 8.5	3195/2910	80	16	31.7	10.4	48.9	OWL
LT285/70R17	121/118S	E	VAT2021	8.5	7.5 - 9.0	3195/2910	80	16	32.8	11.5	52.9	OWL
LT245/75R17	121/118S	E	VAT2019	7.0	6.5 - 7.5	3195/2910	80	16	31.5	9.8	45.9	OWL
LT275/65R18	123/120S	E	VAT2026	8.0	7.5 - 9.0	3415/3085	80	16	32.1	11.0	51.1	OWL
LT275/70R18	125/122S	E	VAT2027	8.0	7.0 - 8.5	3640/3305	80	16	33.2	11.0	52.9	OWL

LI Load Index **SR** Speed Rating **XL** Extra Load **UTQG** Uniform Tire Quality Grade **(s/d)** Single/Dual **LR** Load Range **PR** Ply Rating **BSW** Black Sidewall **OWL** Outlined White Letters

Primewell reserves the right to change the construction, materials or specifications without notice or obligations