VALERA ALL SEASON

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
185/65R14	86H	540 A A	AP427	5.50	5.0 - 6.5	1168	44	10	23.5	7.4	17.2	BSW
195/60R15	88H	540 A A	AP417	6.00	5.5 - 7.0	1235	44	10	24.2	7.9	19.0	BSW
175/65R15	84H	540 A A	AP428	5.00	5.0 - 6.0	1102	44	10	24.0	7.0	17.2	BSW
195/65R15	91H	540 A A	AP386	6.00	5.5 - 7.0	1356	44	10	25.0	7.9	19.8	BSW
205/65R15	94H	540 A A	AP413	6.00	5.5 - 7.5	1477	44	10	25.5	8.2	20.9	BSW
215/70R15	98H	540 A A	AP420	6.50	5.5 - 7.0	1653	44	10	26.9	8.7	23.8	BSW
205/55R16	91H	540 A A	AP383	6.50	5.5 - 7.5	1356	44	10	24.9	8.4	20.5	BSW
215/55R16	93H	540 A A	AP410	7.00	6.0 - 7.5	1433	44	10	25.3	8.9	22.8	BSW
205/60R16	92V	540 A A	AP398	6.00	5.5 - 7.5	1389	44	10	25.7	8.2	22.7	BSW
215/60R16	95H	540 A A	AP395	6.50	6.0 - 7.5	1521	44	10	26.1	8.7	24.4	BSW
225/60R16	98H	540 A A	AP406	6.50	6.0 - 8.0	1653	44	10	26.6	9.0	24.2	BSW
235/60R16	100H	540 A A	AP430	7.00	6.5 - 8.5	1764	44	10	27.1	9.4	27.1	BSW
205/65R16	95H	540 A A	AP401	6.00	5.5 - 7.5	1521	44	10	26.5	8.2	22.9	BSW
215/65R16	98H	540 A A	AP411	6.50	6.0 - 7.5	1653	44	10	27.0	8.7	24.8	BSW
225/65R16	100T	540 A A	AP429	6.50	6.0 - 8.0	1764	44	10	27.5	9.0	25.6	BSW
235/65R16	103T	540 A A	AP424	7.00	6.5 - 8.5	1929	44	10	28.0	9.4	27.6	BSW
215/45R17	87V	540 A A	AP421	7.00	7.0 - 8.0	1201	44	10	24.6	8.4	20.9	BSW
225/45R17	91V	540 A A	AP418	7.50	7.0 - 8.5	1356	44	10	25.0	8.9	24.0	BSW
205/50R17	93V XL	540 A A	AP416	6.50	5.5 - 7.5	1433	50	10	25.1	8.4	22.3	BSW
215/50R17	95V XL	540 A A	AP404	7.00	6.0 - 7.5	1521	50	10	25.5	8.9	24.2	BSW
225/50R17	94V	540 A A	AP399	7.00	6.0 - 8.0	1477	44	10	25.9	9.2	24.8	BSW
235/50R17	96V	540 A A	AP426	7.50	6.5 - 8.5	1565	44	10	26.3	9.6	26.2	BSW
215/55R17	94V	540 A A	AP384	7.00	6.0 - 7.5	1477	44	10	26.3	8.9	25.1	BSW
225/55R17	97V	540 A A	AP402	7.00	6.0 - 8.0	1609	44	10	26.8	9.2	26.0	BSW
235/55R17	99H	540 A A	AP405	7.50	6.5 - 8.5	1709	44	10	27.2	9.6	26.9	BSW
215/60R17	96H	540 A A	AP407	6.50	6.0 - 7.5	1565	44	10	27.2	8.7	24.6	BSW
225/60R17	99H	540 A A	AP390	6.50	6.0 - 8.0	1709	44	10	27.6	9.0	25.8	BSW
235/60R17	102T	540 A A	AP408	7.00	6.5 - 8.5	1874	44	10	28.1	9.4	27.8	BSW
215/65R17	99T	540 A A	AP409	6.5	6.0 - 7.5	1709	44	10	28.0	8.7	25.3	BSW
225/65R17	102H	540 A A	AP382	6.5	6.0 - 8.0	1874	44	10	28.5	9.0	26.4	BSW
235/65R17	104H	540 A A	AP387	7.0	6.5 - 8.5	1984	44	10	29.1	9.4	28.4	BSW
225/45R18	95V XL	540 A A	AP415	7.5	7.0 - 8.5	1521	50	10	26.1	9.0	23.6	BSW
235/45R18	94V	540 A A	AP388	8.0	7.5 - 9.0	1477	44	10	26.3	9.3	26.9	BSW
245/45R18	96V	540 A A	AP422	8.0	7.5 - 9.0	1565	44	10	26.7	9.6	26.0	BSW
225/50R18	95T	540 A A	AP414	7.0	6.0 - 8.0	1521	44	10	26.9	9.2	25.6	BSW
235/50R18	97V	540 A A	AP412	7.5	6.5 - 8.5	1609	44	10	27.3	9.6	27.1	BSW
225/55R18	98V	540 A A	AP396	7.0	6.0 - 8.0	1653	44	10	27.8	9.2	26.4	BSW
235/55R18	100H	540 A A	AP400	7.5	6.5 - 8.5	1764	44	10	28.1	9.6	28.3	BSW
225/60R18	100H	540 A A	AP392	6.5	6.0 - 8.0	1764	44	10	28.6	9.0	26.9	BSW
235/60R18	103V	540 A A	AP385	7.0	6.5 - 8.5	1929	44	10	29.1	9.4	29.5	BSW
245/60R18	105H	540 A A	AP393	7.0	7.0 - 8.5	2039	44	10	29.6	9.8	32.0	BSW
235/65R18	106H	540 A A	AP394	7.0	6.5 - 8.5	2094	44	10	30.0	9.4	30.1	BSW
245/45R19	102V XL	540 A A	AP425	8.0	7.5 - 9.0	1874	50	10	27.7	9.6	27.8	BSW
255/50R19	107V XL	540 A A	AP423	8.0	7.0 - 9.0	2149	50	10	29.1	10.4	31.7	BSW
225/55R19	99V	540 A A	AP403	7.0	6.0 - 8.0	1709	44	10	28.8	9.2	28.0	BSW
235/55R19	101V	540 A A	AP391	7.5	6.5 - 8.5	1819	44	10	29.2	9.6	30.1	BSW
245/45R20	99V	540 A A	AP419	8.0	7.5 - 9.0	1709	44	10	28.7	9.6	29.3	BSW
245/50R20	102V	540 A A	AP389	7.5	7.0 - 8.5	1874	44	10	29.7	10.0	31.5	BSW
235/55R20	102V	540 A A	AP397	7.5	6.5 - 8.5	1874	44	10	30.1	9.5	31.3	BSW

LI Load Index **SR** Speed Rating **XL** Extra Load **UTQG** Uniform Tire Quality Grade **(s/d)** Single/Dual **LR** Load Range **PR** Ply Rating **BSW** Black Sidewall **OWL** Outlined White Letters

Primewell reserves the right to change the construction, materials or specifications without notice or obligations