

VALERA HT

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
P225/70R15	102T	520 A B	AP261	6.5	6.0 - 7.5	1753	44	10	27.4	9.0	26.5	BSW
P225/75R15	102T	520 A B	AP361	6.0	6.0 - 7.5	1874	44	10	28.3	8.8	28.7	BSW
P235/75R15	105T	520 A B	AP320	6.5	6.0 - 8.0	2028	44	10	28.9	9.3	30.4	BSW
P215/70R16	99S	520 A B	AP318	6.5	5.5 - 7.0	1709	44	10	27.9	8.7	26.2	BSW
P225/70R16	101S	520 A B	AP333	6.5	6.0 - 7.5	1819	44	10	28.4	9.0	28.9	BSW
P235/70R16	104T	520 A B	AP317	7.0	6.0 - 8.0	1984	44	10	29.0	9.4	30.6	BSW
P245/70R16	106S	520 A B	AP321	7.0	6.5 - 8.0	2094	44	10	29.5	9.8	31.5	BSW
P255/70R16	109S	520 A B	AP322	7.5	6.5 - 8.5	2271	44	10	30.1	10.2	33.1	BSW
P265/70R16	111T	520 A B	AP355	8.0	7.0 - 9.0	2403	44	10	30.6	10.7	35.1	BSW
P225/75R16	106S XL	520 A B	AP337	6.0	6.5 - 7.5	2094	50	10	29.3	8.8	30.0	BSW
P235/75R16	109S XL	520 A B	AP329	6.5	6.0 - 8.0	2271	50	10	29.8	9.3	31.7	BSW
P245/75R16	109S	520 A B	AP332	7.0	6.5 - 8.0	2271	44	10	30.5	9.8	33.9	BSW
P265/75R16	114T	520 A B	AP356	7.5	7.0 - 9.0	2601	44	10	31.7	10.5	37.0	BSW
225/65R17	102H	520 A B	AP335	6.5	6.0 - 8.0	1874	44	10	28.5	9.0	28.2	BSW
P235/65R17	103T	520 A B	AP319	7.0	6.5 - 8.5	1929	44	10	29.1	9.4	29.5	BSW
P245/65R17	105T	520 A B	AP353	7.0	7.0 - 8.5	2039	44	10	29.5	9.8	30.9	BSW
P265/65R17	110T	520 A B	AP328	8.0	7.5 - 9.5	2337	44	10	30.6	10.7	34.8	BSW
P245/70R17	108T	520 A B	AP354	7.0	6.5 - 8.0	2205	44	10	30.6	9.8	33.7	BSW
P265/70R17	113T	520 A B	AP323	8.0	7.0 - 9.0	2535	44	10	31.7	10.7	36.6	BSW
255/55R18	109H XL	520 A B	AP343	8.0	7.0 - 9.0	2271	50	10	29.0	10.4	33.7	BSW
235/60R18	103V	520 A B	AP351	7.0	6.5 - 8.5	1929	44	10	29.1	9.4	31.1	BSW
245/60R18	105H	520 A B	AP341	7.0	7.0 - 8.5	2039	44	10	29.6	9.8	33.3	BSW
P265/60R18	109T	520 A B	AP327	8.0	7.5 - 9.5	2271	44	10	30.5	10.7	34.4	BSW
235/65R18	106H	520 A B	AP352	7.0	6.5 - 8.5	1984	44	10	30.0	9.4	32.4	BSW
P255/65R18	109T	520 A B	AP350	7.5	7.0 - 9.0	2271	44	10	31.1	10.2	35.1	BSW
P265/65R18	112S	520 A B	AP345	8.0	7.5 - 9.5	2469	44	10	31.5	10.7	35.9	BSW
P275/65R18	114T	520 A B	AP330	8.0	7.5 - 9.5	2601	44	10	32.1	11.0	38.6	BSW
P255/70R18	112T	520 A B	AP347	7.5	6.5 - 8.5	2469	44	10	32.1	10.2	35.7	BSW
P265/70R18	114S	520 A B	AP346	8.0	7.0 - 9.0	2601	44	10	32.6	10.7	38.6	BSW
P245/55R19	103S	520 A B	AP348	7.5	7.0 - 8.5	1929	44	10	29.6	10.0	34.0	BSW
P255/60R19	108H	520 A B	AP342	7.5	7.0 - 9.0	2205	44	10	31.1	10.2	35.5	BSW
275/45R20	110H XL	520 A B	AP075	9.0	8.5 - 10.5	2337	50	10	29.8	10.7	34.6	BSW
265/50R20	107V	520 A B	AP363	8.5	8.0 - 9.0	2150	44	11	30.4	10.9	37.0	BSW
P275/55R20	111H	520 A B	AP325	8.5	7.5 - 9.5	2403	44	10	31.9	11.2	39.2	BSW
P275/60R20	114T	520 A B	AP331	8.0	7.5 - 9.5	2601	44	10	33.0	11.0	39.3	BSW

Tire Size	LI / SR (s/d)	Load Range / Ply Rating	Item Number	Measuring Rim	Rim Width Range	Max. Load (s/d)	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
31X10.50R15LT	109R	C / 6	AP339	8.5	7.5 - 9.0	2270	50	13	30.5	10.6	40.8	BSW
LT225/75R16	115/112S	E / 10	AP357	6.0	6.0 - 7.0	2680/2470	80	13	29.3	8.8	37.3	BSW
LT245/75R16	120/116S	E / 10	AP358	7.0	6.5 - 8.0	3042/2778	80	13	30.5	9.8	42.3	BSW
LT265/75R16	123/120S	E / 10	AP360	7.5	7.0 - 8.0	3415/3085	80	13	31.7	10.5	48.9	BSW
LT285/75R16	126/123R	E / 10	AP083	8.0	7.5 - 8.5	3750/3415	80	13	32.8	11.3	52.0	BSW
LT215/85R16	115/112R	E / 10	AP338	6.0	5.5 - 7.0	2680/2470	80	13	30.4	8.5	38.1	BSW
LT265/75R16	123/120S	E / 10	AP360	7.5	7.0 - 8.0	3415/3085	80	13	31.7	10.5	48.9	BSW
LT245/70R17	119/116S	E / 10	AP349	7.0	6.5 - 8.0	3000/2755	80	13	30.6	9.8	42.6	BSW
LT265/70R17	121/118S	E / 10	AP359	8.0	7.5 - 8.5	3195/2910	80	13	31.7	10.7	47.2	BSW
LT285/70R17	121/118R	D / 8	AP072	8.5	7.5 - 9.0	3195/2910	65	13	32.8	11.5	51.8	BSW
LT245/75R17	121/118R	E / 10	AP336	7.0	6.5 - 7.5	3195/2910	80	13	31.5	9.8	45.4	BSW
LT235/80R17	120/117R	E / 10	AP344	6.5	6.0 - 7.5	3085/2835	80	13	31.8	9.3	43.2	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade (s/d) Single/Dual LR Load Range PR Ply Rating BSW Black Sidewall OWL Outlined White Letters

Primewell reserves the right to change the construction, materials or specifications without notice or obligations